RADA





CLIP, WALK AND TALK WITH RADA DUO

KEY FEATURES:

Wireless UHF System

Effective range of up to 50 meters

Plug & Play

No Drivers or Software Needed 2 Transmitters 1 Receiver

DUO

MICS

Transmitters Work Simultaneously

CONNECTION DIAGRAM



TECHNICAL SPECIFICATIONS

| RADA Duo Transmitter Microphone | |
|---------------------------------|---|
| Transmission | UHF |
| Voltage | 3.7V lithium battery |
| Current | 100mA@3.8VDC |
| Microphone type | omni-directional |
| Frequency | 650~690MHz |
| Frequency stability | <15ppm |
| Transmission power level | 13dBm/3.8VDC |
| Frequency response | 50Hz~15K Hz |
| Operating distance | 50 meters, depending on the environment |
| Battery capacity | 3.7V/480mAh |
| Time to full charge | 1.5 hours |
| Endurance rating | approximately 4 hours |
| Net weight | approximately 70g |

| RADA Duo Receiver | |
|---------------------|--|
| Frequency | 650~690MHz |
| Frequency stability | < ± 15ppm |
| Distortion | < 0.5% |
| Audio Delay | < 2.5ms |
| Frequency response | 50Hz~15K Hz |
| Sensitivity | < -105dBm |
| Dynamic range | >85dB |
| Operating distance | 50 meters to 90 meters, depending on the environment |
| Battery capacity | 3.7V/800mAh |
| Time to full charge | 2 hours |
| Endurance rating | approximately 6 hours |
| Net weight | approximately 86g |
| Dimensions | 62mm X 42mm X 16mm |