

	LS-2 (VA1)	LS-US2	LS-110	LS-200 (VA1)	LS-300 (VA1)	KL-3T (VA1)	LS-400 (VA1)	LS-860	LS-410	
Media Station										
Channels	2				3		4		4* *2 channels maximum in 4K mode	
Max. Simultaneous RTMP Streams Out	1		2							
Simultaneous Recording Mixed + Original Sources	✓								✓* *Mixed only in 1080p50/60 and 4K modes	
Video inputs	x2 HDMI/VGA, IP sources (RTP/RTSP/RTMP/ONVIF S)	x2 USB-A or x1 USB-A and x1 USB-microB, IP sources (RTP/RTSP/RTMP/ONVIF S/NDI-HX*) *in LS-US2N only	x1 HDMI, IP sources (RTP/RTSP/RTMP/ONVIF S)	x2 HDMI/VGA, IP sources (RTP/RTSP/RTMP/ONVIF S)			x4 HDMI, IP sources (RTP/RTSP/RTMP/ONVIF S/NDI-HX*) *in LS-860N only	x2 HDMI, x1 USB-A, IP sources (RTP/RTSP/RTMP/ONVIF S/SRT (push))		
Audio inputs	x1 Line in, x2 HDMI, x1 USB, IP sources (RTP/RTMP)	x1 USB, IP sources (RTP/RTSP (AAC)/RTMP/NDIHX*) *in LS-US2N only	x1 Line in, x1 HDMI, x1 USB, IP sources (RTP/RTMP)	x1 Line in, x1 Mic in, x2 HDMI, x1 USB, x1 Phoenix, IP sources (RTP/RTMP)			x4 Configurable Line/Mic in, x4 HDMI, x1 USB, x1 Phoenix, IP sources (RTP/RTMP/NDIHX*) *in LS-860N only	x1 Line in, x1 Mic in, x2 HDMI, x1 USB, x1 Phoenix, IP sources (RTP/RTSP (AAC)/RTMP/SRT (push), NDIHX, Dante 2x2)		
Control	RS-232/TCP/API/Numeric Keypad/Interactive GUI/Mobile Device Adapted Interface /ARECloud	TCP/API/Numeric Keypad/Interactive GUI/Mobile Device Adapted Interface/ARECloud/Online Director Web Interface	RS-232/TCP/API/Numeric Keypad/Interactive GUI/Mobile Device Adapted Interface/ARECloud/Online Director Web Interface							
PTZ Cameras Control	Pelco D and P, VISCA, ONVIF S, VISCA over IP	VISCA over IP, ONVIF S, NDIHX* *in LS-US2N only	Pelco D and P, VISCA, ONVIF S, VISCA over IP				Pelco D and P, VISCA, ONVIF S, VISCA over IP, NDIHX* *in LS-860N only	Pelco D and P, VISCA, ONVIF S, VISCA over IP, NDIHX		
Internal and other Storage	64 GB, NAS support	No internal storage (32 GB drive included), NAS support	64 GB, NAS support	1 TB, NAS support			2 TB, NAS support			
Backup	FTP/SFTP/Google Drive	FTP/SFTP/OpenCast/Kaltura/Panopto/Google Drive								
Background Images	✓									
Overlay Images	✓									
Themes	✓									
Special Feature	Budget rack solution, LAN inputs, HDMI/VGA outputs	Compact one-button exterior, USB video inputs, DP and HDMI outputs, LAN input LS-US2N version supports NDIHX Can admit 4K inputs	Compact, 4K input and 4K 60 FPS loop-through HDMI outputs Can admit 4K inputs	LAN inputs, HDMI/VGA outputs includes rack mounts		Embedded 10" touch display, LAN inputs, HDMI/VGA outputs	LAN inputs, HDMI/VGA outputs, includes rack mounts and a USB numeric keypad	Multiple HDMI inputs and outputs, 1080p60 FPS mode, can define specific audio channel for individual video channel recording, SRT support (Caller and Listener modes), includes rack mounts, USB numeric keypad, and wireless content sharing accessory ARECast. LS-860N version supports NDIHX	2160p30, 1080p30 and 1080p60 modes and AVC/HEVC modes* HDMI, LAN, and USB video inputs, HDMI/DP outputs. Supports NDIHX, SRT (Caller and Listener modes), and Dante Audio 2x2 *HEVC mode does not support streaming. 1080p50/60 mode does not support individual video channel recording and individual preview. 2160p30 mode does not support individual video channel recording, individual preview, separate recording/streaming profiles, and DP output	